

TechCheck PLUS

Moisture Meter for Building Materials

Designed to Scan and Locate moisture levels in wood, concrete, sheetrock and other building materials

Given the challenging conditions of building inspection, installation, and drying jobs, it pays to have an easy-to-use moisture meter that you can depend on. The easy-to-use 2-in-1 **TechCheck PLUS** was designed with simplicity in mind and helps to make even the most demanding job simple. The newly updated **TechCheck PLUS** has all the great features you've come to expect, along with some new ones.

Features:

- Bright, clear digital display
- Spanish language option
- Built-in back-light makes reading in dark places a cinch
- Auto-shutoff timer saves battery life
- Audible, adjustable alarm alerts you when your pre-selected MC has been reached
- Rugged construction ensures years of reliable use
- Sturdy plastic carrying case
- 9V battery
- 1-year warranty



Specifications:

Battery : (1) 9-V Alkaline
Sizes : 22 x 9 x 4,5 cms
8½" x 3 3/8" x 1¾"
Weight: 312 g. (11 oz)

Pin mode:

- 0.1% - 6% drywall scale, Delmhorst Exclusive
- 6%-60% MC wood scale
- Integral Contact pins mounted on top of meter provide 5/16" penetration
- Built-in connector accepts any Delmhorst electrode

Scan Mode: (0-300 numerical reference scale)

One-year warranty on instrument, 3 months on electrodes

MoistureCheck Package Variations:

TechCheckW/CS:

Includes meter, carrying case and additional contact pins

TechCheck/PKG:


Includes meter, carrying case and additional contact pins including 21-E electrode

TechCheck PLUS Moisture Meter for Building Materials

Available Electrodes

26-ES

The 26-ES has contact pins with insulated shanks. Only the tips are exposed. The pins make contact with the material only at their uncoated tip and provide much more accurate readings of moisture content at various levels of penetration. This feature allows you to penetrate through flooring to a concrete or plywood subfloor.

21-E

Features #608, insulated pins for use on insulation or any tests where deeper penetration (8cm (3,25")) is required.

2-E

Uses the same contact pins that are mounted on each meter. This electrode is great to use in hard to reach places. Ideal for the home inspector and pest control operator.

19-E/STC

Two 12,5 cm (5") long blades, bent to a 35° angle. Teflon coated with exposed tips. Used to check behind trim and baseboard molding.