

The F-2000 is great for hay producers looking to enhance quality control. The F-2000 checks hay moisture in the windrow or in bales, and comes with the same accuracy and clarity as the FX-2000



**F-2000 – Features**

- Bright, clear digital display
- Averages up to 100 accumulated readings
- Displays average and highest of accumulated readings
- Moisture Range: 6%-40% on hay
- Built-in calibration check
- Audible, adjustable alarm alerts you when a pre-selected MC has been reached
- Rugged construction ensures years of reliable use
- Optional sturdy plastic carrying case


**Specifications:**

Battery : (1) 9-V Alkaline  
 Sizes : 19 x 8 x 4,5 cms.  
 Weight : 540 g.

3-year warranty on instrument, 3 months on electrodes

**Available Electrodes**

- 1235** 25 cms. Prod used for testing standard bales. Attaches directly to the connector. Also available in 45 cms (18") length (**1235/18**)
- 831** Short pin prod. For testing hay in the windrow (requires H-4 Handle)
- 830-2** 25 cms (10") Prod - for testing standard and high density bales. Use with H-4 Handle
- 830-3** 45 cms (18") Prod - for testing hay in large bales or round bales. Use with H-4 Handle
- 830-4** 90 cms (36") Prod - for testing hay in large bales or round bales. Use with H-4 Handle
- H-4** Mounts to the connector on the top of any meter to use the 830 series and 831 prods. This arrangement is recommended when testing any high density or larger bales to minimize stress placed on the meter case
- 324CAS** The case fits all components shown. Will not hold the 1986 bale sensor or the 830-3 and 830-4 prods



1235



H-4



831



830