

F6 F-6/6-30 Moisture Meter for Hay and Straw

Designed to measure moisture content in Hay and Straw

With simplified controls, the F6 and F-6/6-30 are great entry-level meters for value-minded hay producers. It is also a favorite among those serving the export markets that require lower MC range readings



F6 and F-6/6-30 – Features

- Easy-to-read analog display
- Moisture Range:
 - F6: 13%-40% MC range
 - F6/6-30: 6%-30% MC range
- Built-in calibration check
- Rugged construction ensures years of reliable use
- Optional sturdy plastic carrying case

Specifications:

Battery : (1) 9-V Alkaline
 Sizes : 19 x 8 x 4,5 cms.
 Weight : 540 g.

One-year warranty on instrument, 3 months on electrodes

Available Electrodes

- 1235** 25 cms. Prod used for testing standard bales. Attaches directly to the connector. Also available in 45 cms (18") length (**830-3/C168**)
- 831** Short pin prod. For testing hay in the windrow (requires H-4 Handle)
- 830-2** 25 cms (10") Prod - for testing standard and high density bales Use with H-4 Handle
- 830-3** 45 cms (18") Prod - for testing hay in large bales or round bales Use with H-4 Handle
- 830-4** 90 cms (36") Prod - for testing hay in large bales or round bales Use with H-4 Handle
- H-4** Mounts to the connector on the top of any meter to use the 830 series and 831 prods. This arrangement is recommended when testing any high density or larger bales to minimize stress placed on the meter case
- 324CAS** The case fits all components shown. Will not hold the 1986 bale sensor or the 830-3 and 830-4 prods



1235



H-4



831



830

