

FX-2000 Moisture Meter for Hay and Straw

Designed to measure moisture content in Hay and Straw

This state-of-the-art meter is ideal for high-volume producers who need the time-saving convenience of on-the-go monitoring. Whether in the windrow, on-the-go while baling, or in the bale, the FX-2000 gives clear, accurate moisture readings every step of the way!



- Bright, clear digital display
- Can be used for on-the-go moisture monitoring or as a portable meter
- In continuous mode:
 - Takes two readings every second.
 - Displays the average and highest of eight accumulated readings
 - Readings updated every 4 seconds
 - Built-in back light
 - Connects to tractor power supply
- In portable mode:
 - Averages up to 100 accumulated readings
 - Displays average and highest of accumulated readings
- Moisture Range: 6%-40% on hay
- Built-in calibration check
- Audible, adjustable alarm alerts you when a pre-selected MC has been reached
- Rugged construction ensures years of reliable use
- Optional sturdy plastic carrying case

Specifications:

Battery : (1) 9-V Alkaline
 Sizes : 19 x 8 x 4,5 cms.
 Weight : 540 g.

3-year warranty on instrument, 3 months on electrodes

1235

25 cms. Prod used for testing standard bales. Attaches directly to the connector. Also available in 45 cms (18") length (**1235/18**)

1986

For continuous monitoring during baling. Comes with 9 mtr. (30ft) cable to run from the sensor mounted in the bale chamber to the meter in the cab. May be used with any model, but is recommended to use with Model FX-2000. Also available as **1986/40** with 12 mtr. (40ft) cable for larger balers.

831

Short pin prod. For testing hay in the windrow (requires H-4 Handle).

830-2

25 cms Prod - for testing standard and high density bales. Use with H-4 Handle.

830-3

45 cms Prod - for testing hay in large bales or round bales. Use with H-4 Handle.

830-4

90 cms Prod - for testing hay in large bales or round bales. Use with H-4 Handle.

H-4

Mounts to the connector on the top of any meter to use the 830 series and 831 prods. This arrangement is recommended when testing any high density or larger bales to minimize stress placed on the meter case.

324CAS

The case fits all components shown. Will not hold the 1986 bale sensor or the 830-3 and 830-4 prods.



1235



H-4



831



830

